



### Construction

Brass Body (CuZn38Pb18); ABS handle

### Finishes

Chrome plated to BS EN 248

### Product Type

Contemporary

### Water Pressure

Min. 0.5 bar, Max. 6.0 bar

### Plumbing Systems

Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1

### Standards

Complies with BSEN 1111

### Cartridge

On/Off - Alfano

Thermostatic - Agua

### Fitting

Easy Fit Kit

### Valve

Integrate diverter ceramic valve

### Check Valve

0.5-10 gpm

### Additional Information

1. Temperature: Pre-set 38°C, with push button override to 48°C.
2. Automatic shut off in the event of hot or cold water supply failure.
3. Shower head: Chrome, Ø200mm, Stainless Steel
4. Shower handset: Chrome, 3 mode, ABS
5. Shower hose: Stainless steel, 1.5m
6. Riser Rail: Adjustable height riser rail



### Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
	3.5	5.0	6.1	8.0	11.4	14.0	16.2	19.8	22.8	25.4

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.