



**Construction**

Brass Body

**Finishes**

Chrome

**Product Type**

Contemporary

**Water Pressure**

Min. 0.5 bar, Max. 6.0 bar

**Plumbing Systems**

Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1

**Standards**

Complies with BSEN 1111

**Cartridge**

On/Off - Alfano

**Fitting**

Easy Fit

**Additional Information**

1. Temperature: Pre-set 38°C, with push button override to 48°C.
2. Automatic shut off in the event of hot or cold water supply failure.
3. Shower head : Chrome , Ø200mm, Stainless Steel
4. Shower handset : Chrome , single mode, ABS
5. Shower hose : Chrome, stainless steel , double interlock, 1.5m



**Flow Rates** (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
<b>MLSHFLSQ</b>	2.2	4.8	-	8.1	13.2	-	-	22.6	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.