



#### Construction

Brass Body (CuZn40Pb18)

#### Finishes

Chrome plated to BS EN 248

#### Product Type

Contemporary

#### Water Pressure

Min. 0.5 bar, Max. 6.0 bar

#### Plumbing Systems

Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1

#### Standards

Complies with BSEN 1111

#### Cartridge

Thermostatic

#### Fitting

Escutcheon

#### Guarantee

10 years against manufacturing faults (3 Years on Serviceable Parts).

#### Additional Information

1. Temperature: Pre-set 38°C, with push button override to 48°C.
2. Automatic shut off in the event of hot or cold water supply failure.
3. Shower head: Chrome, Ø200mm, ABS
4. Shower handset: Chrome, 3 mode, ABS
5. Shower hose: Chrome, stainless steel, double interlock, 1.5m

#### Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
VM09	-	6.0	-	9.5	12.9	-	17.0	-	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.