



## Construction

## Finishes

## Product Type

## Water Pressure

## Plumbing Systems

## Standards

## Cartridge

## Aerator

## Fitting

## Guarantee

## Additional Information

Brass Body CuZn40Pb2, EN CW617N (equivalent to BS CZ122)

Chrome plated to BS EN 248

Contemporary

Min. 0.2 bar, Max. 6.0 bar

Suitable for all plumbing systems

Complies with BS6920, BS EN200

35mm Coolstart ceramic disc cartridge

Neoperl Adjustable Slim Air

UK: M10 x 350mm ½" BSP Female Flexi Tails

EU: M10x350mm 3/8" BSP Female Flexi Tails.

10 years against manufacturing faults (3 Years on Serviceable Parts).

Supplied with G 1¼" sprung waste

## Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
MLTADA7	-	3.2	-	6	7.8	-	10.8	-	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.