



<b>Construction</b>	Brass Body (CuZn38Pb18); Zinc alloy handle
<b>Finishes</b>	Chrome : Ni : 8-12um, Cr : 0.25-0.3um
<b>Product Type</b>	Contemporary
<b>Water Pressure</b>	Min. 0.5 bar, Max. 6.0 bar
<b>Plumbing Systems</b>	Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1
<b>Standards</b>	Complies with BSEN 1111
<b>Check valve</b>	Neoperl
<b>Aerator</b>	Neoperl Aerator
<b>Cartridge</b>	Thermostatic, Integrate diverter ceramic valve
<b>Fitting</b>	3/4" BSP deck mounted pillars
<b>Guarantee</b>	10 years against manufacturing faults (3 Years on Serviceable Parts).

- Additional Information**
1. Temperature: Pre-set 38°C, with push button override to 48°C.
  2. Automatic shut off in the event of hot or cold water supply

**Flow Rates** (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
	6.2	7.0	-	9.6	12.6	-	17.4	22.0	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.