



<b>Construction</b>	Brass Body, Zinc Alloy Handle
<b>Finishes</b>	Chrome plated to BS EN 248
<b>Product Type</b>	Contemporary
<b>Water Pressure</b>	Min. 0.1 bar, Max. 6.0 bar
<b>Plumbing Systems</b>	Suitable for all plumbing systems
<b>Standards</b>	Complies with BS5412, BS EN200
<b>Cartridge</b>	40mm ceramic disc cartridge
<b>Aerator</b>	Aerator spout
<b>Fitting</b>	M12 x 350mm ½" BSP Female Flexi Tails
<b>Guarantee</b>	10 years against manufacturing faults (3 Years on Serviceable Parts).

**Additional Information** Supplied with sprung waste chrome plated

Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
	3.8	4.6	-	6.1	8.3	10.1	11.5	14.2	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.