

CONSTRUCTION	Brass Body						
FINISHES	Brushed Brass PVD Finish						
PRODUCT TYPE	Contemporary						
WATER PRESSURE	Min. 1.0 Bar, Max. 6.0 Bar						
PLUMBING SYSTEMS	Suitable for all plumbing systems, Hot and Cold water pressure preferably balanced. Max. supply pressure differential requirement no greater than 5:1						
STANDARDS	Complies with BS 6920, BS EN 200						
CERTIFICATION	Manufactured to Comply with WRAS (approval pending)						
CARTRIDGE	Citec Cartridge						
AERATOR	Neoperl Aerator						
FITTING	Easy-Plumb Box						
FLEXI TAILS	Tucai WRAS						
MORE INFO	PVC Hose & Triple Function Handset						



Flow Rates (Litres per minute)

SYSTEM	0.1	0.2	0.3	0.5	1.0	1.5	2.0	3.0	4.0	5.0
PRESSURE	Bar	Bar	Bar	Bar	Bar	Bar	Bar	Bar	Bar	Bar
	1.38	2.93	4.25	6.32	9.98	12.91	15.35	19.15	22.43	

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.

## f 🞯 J in 🤊 🗗