



- | | |
|-------------------------------|---|
| Construction | Brass Body (CuZn38Pb18) |
| Finishes | Matt Black |
| Product Type | Contemporary |
| Water Pressure | Min. 0.2 bar, Max. 6.0 bar |
| Plumbing Systems | Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1 |
| Standards | Complies with BSEN 1111 |
| Cartridge | Thermostatic |
| Fitting | Inlet: 3/4" female thread
Outlet: 1/2" Female thread |
| Guarantee | 10 years against manufacturing faults (3 Years on Serviceable Parts). |
| Additional Information | 1. Temperature: Pre-set 38°C, with push button override to 48°C.
2. Automatic shut off in the event of hot or cold water supply failure. |

Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
	-	7.9	-	12.6	20.0	-	-	36.0	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.