




f 🞯 J in 🤊 🗗

CONSTRUCTION	Brass Body (CuZn40Pb2), EN CW617N (equivalent to BS CZ122)					
FINISHES	Matt Black Electro Plated					
PRODUCT TYPE	Contemporary					
WATER PRESSURE	Min. 0.5 bar, Max. 6.0 bar					
PLUMBING SYSTEMS	Suitable for all plumbing systems, max. supply pressure differential requirement no greater than 5.1					
STANDARDS	Complies with BS5412 & BS EN200					
CERTIFICATION	Manufactured to comply with WRAS					
AERATOR	Neoperl					
FITTING	Brass G3/4" BSP Tails					
ADDITIONAL	Triple Function Push Button Handset					
INFORMATION	PVC Antibacterial Hose					









Flow Rates (Litres per minute)

SYSTEM PRESSURE	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
Spout	5.1	-	8.0	10.0	13.9	-	19.5	23.6	27.2	30.4
Handset	11.2	-	16.7	20.7	28.5	-	40.7	48.2	54.5	63.5

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.