58

Max 40 - Min



f 🞯 J in 🤊 🗗

CONSTRUCTION	Brass Body						
FINISHES	Brushed Brass PVD Finish						
PRODUCT TYPE	Contemporary						
WATER PRESSURE	Min. 0.2 bar, Max. 6.0 bar						
PLUMBING SYSTEMS	Suitable for all plumbing systems, max. supply pressure differential requirement no greater than 5.1						
STANDARDS	Complies with BS6920 & BS EN200						
CERTIFICATION	Manufactured to comply with WRAS						
CARTRIDGE	Citec						
AERATOR	Neoperl						
FITTING	Tucai WRAS Flexi						
ADDITIONAL INFORMATION	Universal Basin Waste included						

114 3 119 122 01 $\Box 50$ M32X1.5 e. 31-1/4

Flow Rates (Litres per minute)

SYSTEM	0.1	0.2	0.3	0.5	1.0	1.5	2.0	3.0	4.0	5.0
PRESSURE	Bar	Bar	Bar							
	2.2	-	-	4.2	5.9	-	8.8	10.2	11.7	

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.